

the Administrator related to the aircraft design for sustained engine rotor imbalance conditions provisions of 14 CFR part 25 regarding the type certification requirements for transport airplane structure. This notice is necessary to give all interested persons an opportunity to present their views on the proposed AC.

DATES: Comments must be received on or before July 10, 2000.

ADDRESSES: Send all comments on the proposed AC to: Federal Aviation Administration, Attention: Jim Haynes, Airframe/Airworthiness Branch, ANM-115, Transport Airplane Directorate, Aircraft Certification Service, 1601 Lind Avenue SW, Renton, WA 98055-4056. Comments may also be submitted electronically to the following address: jim.haynes@faa.gov. Comments may be inspected at the above address between 7:30 a.m. and 4:00 p.m. weekdays, except Federal holidays.

FOR FURTHER INFORMATION CONTACT: Jim Haynes, Airframe/Airworthiness Branch, ANM-115, Transport Airplane Directorate, Aircraft Certification Service, 1601 Lind Avenue SW, Renton, WA 98055-4056; telephone (425) 227-2131; facsimile (425) 227-1320. Questions may also be submitted electronically to the following address: jim.haynes@faa.gov.

SUPPLEMENTARY INFORMATION:

Comments Invited

You may obtain an electronic copy of the advisory circular identified in this notice at the following Internet address: www.faa.gov/avr/air/airhome.htm. If you do not have access to the Internet, you may request a copy by contacting Susan Boylon, Program Management Branch, ANM-114, FAA Transport Airplane Directorate, Aircraft Certification Service, 1601 Lind Avenue SW., Renton, WA 98055-4056; telephone (425) 227-1152. Interested persons are invited to comment on the proposed AC by submitting such written data, views, or arguments, as they may desire. Commenters should identify AC 25-XX, and submit comments, in duplicate, to the address specified above. All communications received on or before the closing date for comments will be considered by the Transport Standards Staff before issuing the final AC.

Discussion

This AC contains guidance for the latest amendment of the regulations and applies to all transport category airplanes for which a new, amended, or supplemental type certificate is required. This guidance should be

applied to any portion of the airplane structure that has been modified. In the past, advisory and guidance information applicable to transport airplane structure has been published as AC's. Advisory circulars have not been developed for all of the regulatory requirements applicable to transport airplane structure, however. In many instances, certification of new technology airplanes resulted in the need to interpret the existing regulations and to apply new regulations. Issue papers and special conditions were generated to document the compliance method agreed upon between the applicant and the FAA. In other instances, applicants, FAA Aircraft Certification Office (ACO) managers, and foreign regulatory authorities have requested interpretation of the intent of specific regulations. This guidance was documented in the form of policy memorandums that were distributed to all ACO's, letters to applicants and foreign airworthiness authorities, and issue papers. In many instances, this information was not organized in a manner that allowed easy access, and applicants were not aware of revised policy. This AC formalizes existing policy so that the public and FAA personnel have access to this information. The methods and procedures described in this AC have evolved after many years and represent current certification practice.

Issued in Renton, Washington, on May 8, 2000.

Vi L. Lipski,

Acting Manager, Transport Airplane Directorate, Aircraft Certification Service, ANM-100.

[FR Doc. 00-12311 Filed 5-15-00; 8:45 am]

BILLING CODE 4910-13-M

DEPARTMENT OF TRANSPORTATION

Federal Railroad Administration

Petition for Waiver of Compliance

In accordance with part 211 of Title 49 Code of Federal Regulations (CFR), notice is hereby given that the Federal Railroad Administration (FRA) received a request for a waiver of compliance with certain requirements of its safety standards. The individual petition is described below, including the party seeking relief, the regulatory provisions involved, the nature of the relief being requested, and the petitioner's arguments in favor of relief.

The Texas Mexican Railway Company

[Waiver Petition Docket Number FRA-2000-7040]

The Texas Mexican Railway Company (TM) seeks a permanent waiver of compliance from certain provisions of the Safety Appliances Standards, 49 CFR part 231, and the Power Brakes and Drawbars regulations, 49 CFR part 232, concerning RoadRailer® train operations over their railroad system. Specifically, TM requests relief from the requirements of 49 CFR part 231, which specifies the number, location and dimensional specifications for handholds, ladders, sill steps, uncoupling levers, and handbrakes; and § 232.2, which regulates drawbar height.

TM would like to begin operations of RoadRailer® equipment over its system in connection with the Burlington Northern Santa Fe Railway (BNSF) and/or the Kansas City Southern Railroad to and from interchange with the Transportation Ferroviaria Mexicana at Laredo, Texas, with movement of the equipment between interchange points at Beaumont, Houston, or Corpus Christi, Texas. TM requests that FRA consider this waiver under the same conditions as granted to BNSF under Docket Number FRA 1999-5895.

Interested parties are invited to participate in these proceedings by submitting written views, data, or comments. FRA does not anticipate scheduling a public hearing in connection with these proceedings since the facts do not appear to warrant a hearing. If any interested party desires an opportunity for oral comment, they should notify FRA, in writing, before the end of the comment period and specify the basis for their request.

All communications concerning these proceedings should identify the appropriate docket number (e.g., Waiver Petition Docket Number 1999-5894) and must be submitted to the Docket Clerk, DOT Docket Management Facility, Room PL-401 (Plaza Level), 400 7th Street, SW, Washington, DC 20590. Communications received within 15 days of the date of this notice will be considered by FRA before final action is taken. Comments received after that date will be considered as far as practicable. All written communications concerning these proceedings are available for examination during regular business hours (9:00 a.m.-5:00 p.m.) at the above facility. All documents in the public docket are also available for inspection and copying on the Internet at the docket facility's web site at <http://dms.dot.gov>.

Issued in Washington, DC, on May 9, 2000.

Michael J. Logue,

Deputy Associate Administrator for Safety Compliance and Program Implementation.

[FR Doc. 00-12313 Filed 5-15-00; 8:45 am]

BILLING CODE 4910-06-P

DEPARTMENT OF TRANSPORTATION

National Highway Traffic Safety Administration

[Docket No. NHTSA-2000-7312; Notice 1]

General Motors North America, Notice of Application for Decision of Inconsequential Noncompliance

General Motors North America (GM) has determined that on some 1995-1999 model year GMC and Chevrolet trucks and on some 1997-1999 Pontiac Grand Prix cars, the center high-mounted stop lamp (CHMSL) could briefly illuminate if the hazard flasher switch is depressed to its limit of travel. This condition would not meet the lighting requirements of S5.5.4 of Federal Motor Vehicle Safety Standard (FMVSS) No. 108, "Lamps, reflective devices, and associated equipment." Pursuant to 49 U.S.C. 30118(d) and 30120 (h), GM has petitioned for a determination that this condition is inconsequential to motor vehicle safety and has filed an appropriate report pursuant to 49 CFR part 573, "Defect and Noncompliance Reports."

We are publishing this notice of receipt of an application as required by 49 U.S.C. 30118 and 30120. This action does not represent any agency decision of other exercise of judgment concerning the merits of the application.

FMVSS No. 108 establishes the requirements for signaling to enable safe operation in darkness and other conditions of reduced visibility. Under S5.5.4 of FMVSS No. 108, the CHMSL on each vehicle shall be activated only upon application of the service brakes. During Model Year 1995-1999 GM produced 3,375,393 vehicles with a CHMSL that could briefly illuminate if the hazard flasher switch is depressed to its limit of travel. The vehicles that may have this condition are 1995-1999 model year GMC and Chevrolet trucks and some 1997-1999 Pontiac Grand Prix cars.

GM supports its application for inconsequential noncompliance by stating the following:

The possibility of unintended CHMSL illumination is very low, for several reasons. Hazard flashers are infrequently used in service. The condition can occur only when the hazard flasher switch is at the extreme bottom of travel. To turn the hazard flashers

on or off, one need merely push the hazard flasher switch. It is not necessary to push the switch all the way to its limit of travel. Even when the switch is depressed all the way to its limit of travel, CHMSL illumination may not occur. In approximately 50% of the switches it would be moderately difficult to get a CHMSL activation. With these switches, it is also necessary to apply a side force to the hazard flasher switch (in addition to having the switch at its bottom of travel) before the CHMSL might illuminate.

Even if the condition does occur, the duration of unintended CHMSL illumination would be very brief. The hazard flasher switch requires less than a second in total to turn the flashers on or off, and only for a fraction of this total time would the switch be all the way to its limit of travel.

About one-third of the affected vehicles have incandescent CHMSLs. In these vehicles, visible illumination of the CHMSL would not occur unless the hazard switch were depressed to its full limit of travel and held there long enough for the incandescent bulb filaments to heat and become visible. Therefore, unless the hazard switch was deliberately held at its limit of travel, and possibly with a side force, any unintended CHMSL illumination would be momentary and as a practical matter virtually imperceptible.

Even if a visible CHMSL illumination occurs upon hazard flasher activation, it would almost certainly have no adverse effect on safety. Hazard flasher lights are typically used when the vehicle is off the road or out of traffic. However, if a CHMSL illuminated due to this condition when the vehicle was on the road, a following driver would likely see a brief single flash of the CHMSL. As a practical matter, the following driver might not notice this flash at all. Even if he or she did, there would seem to be no likelihood of driver confusion or inappropriate responses. In reaching this view, we have considered the following situations and would invite the agency's consideration of them as well:

A driver who turns on the hazard flasher switch does so in order to alert others to some situation that the driver judges to be a highway safety hazard. Indeed, the owner's manual in each of these vehicles states as much: Your hazard warning flashers let you warn others. They also let police know you have a problem.

When the driver turns them on, the hazard lamps on these vehicles commence flashing immediately after the driver releases the switch. In this situation, any momentarily illuminated CHMSL would augment the hazard alert to following drivers.

If the hazard flasher switch is being turned off, the CHMSL could be illuminated momentarily while the hazard lamps are flashing. A following driver is unlikely to react inappropriately to a momentary CHMSL illumination when two hazard lamps are already flashing.

In many situations, it seems likely that a driver suddenly approaching a hazard situation might want to slow down, and therefore the service brakes would be applied when the hazard switch is depressed. In this case, the CHMSL would remain illuminated

by the service brakes as required by FMVSS 108. This situation would pose no safety or compliance issue because the CHMSL would already be on.

The CHMSL (and the remainder of the vehicle lighting) otherwise meets all of the requirements of FMVSS 108.

GM is not aware of any accidents, injuries, owner complaints or field reports for the subject vehicles related to this condition.

NHTSA has previously granted inconsequential treatment for a similar condition. In 1995, General Motors petitioned for inconsequential treatment for a noncompliance while the hazard switch was being used (reference Mr. Milford Bennett letter to Dr. Ricardo Martinez dated June 16, 1995). The agency subsequently granted inconsequential treatment for this condition (reference Docket 95-57, Notice 2 published in the **Federal Register**, 61 FR 2865, January 29, 1996). No one opposed the application. NHTSA found in that situation that "the transient activation of the CHMSL, a false signal, is highly unlikely to mislead a following driver," at 2865-2866.

The current situation would appear to be even less of a highway safety issue, because (a) the previous condition could occur at various positions within the normal operating travel of the hazard switch, while the current condition can only occur at the extreme bottom of travel of the hazard switch; and (b), the previous condition could involve up to three momentary flashes of the CHMSL, while the current condition only has the potential for a single momentary illumination of the CHMSL.

Interested persons are invited to submit written data, views, and arguments on the application described above. Comments should refer to the docket number and be submitted to: U.S. Department of Transportation, Docket Management, Room PL-401, 400 Seventh Street, SW, Washington, DC, 20590. It is requested that two copies be submitted.

All comments received before the close of business on the closing date indicated below will be considered. The application and supporting materials, and all comments received after the closing date, will also be filed and will be considered to the extent possible. When the application is granted or denied, the notice will be published in the **Federal Register** pursuant to the authority indicated below. Comment closing date: June 15, 2000.

(49 U.S.C. 301118, 301120; delegations of authority at 49 CFR 1.50 and 501.8)

Issued on: May 10, 2000.

Stephen R. Kratzke,

Associate Administrator for Safety Performance Standards.

[FR Doc. 00-12312 Filed 5-15-00; 8:45 am]

BILLING CODE 4910-59-P