Rules and Regulations

Federal Register

Vol. 68, No. 1

Thursday, January 2, 2003

This section of the FEDERAL REGISTER contains regulatory documents having general applicability and legal effect, most of which are keyed to and codified in the Code of Federal Regulations, which is published under 50 titles pursuant to 44 U.S.C. 1510.

The Code of Federal Regulations is sold by the Superintendent of Documents. Prices of new books are listed in the first FEDERAL REGISTER issue of each week.

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 23

[Docket No. CE188, Special Condition 23-131-SC]

Special Conditions; Rockwell Collins, Incorporated on the Raytheon Model B300/B300C; Protection of Systems for High Intensity Radiated Fields (HIRF)

AGENCY: Federal Aviation Administration (FAA), DOT.

ACTION: Final special conditions; request

for comments.

SUMMARY: These special conditions are issued to Rockwell Collins, Cedar Rapids, Iowa 52498 for a Supplemental Type Certificate for the Raytheon Model B300/B300C airplanes. This airplane will have novel and unusual design features when compared to the state of technology envisaged in the applicable airworthiness standards. These novel and unusual design features include the installation of a ProLine 21 avionics system, which includes an electronic flight instrument system (EFIS) display for which the applicable regulations do not contain adequate or appropriate airworthiness standards for the protection of these systems from the effects of high intensity radiated fields (HIRF). These special conditions contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to the airworthiness standards applicable to this airplane. **DATES:** The effective date of these special conditions is December 18, 2002. Comments must be received on or before February 3, 2003.

ADDRESSES: Comments may be mailed in duplicate to: Federal Aviation Administration, Regional Counsel, ACE-7, Attention: Rules Docket Clerk, Docket No. CE188, Room 506, 901 Locust, Kansas City, Missouri 64106. All

comments must be marked: Docket No. CE188. Comments may be inspected in the Rules Docket weekdays, except Federal holidays, between 7:30 a.m. and

FOR FURTHER INFORMATION CONTACT: Wes Ryan, Aerospace Engineer, Standards Office (ACE-110), Small Airplane Directorate, Aircraft Certification Service, Federal Aviation Administration, 901 Locust, Room 301, Kansas City, Missouri 64106; telephone (816) 329-4127.

SUPPLEMENTARY INFORMATION: The FAA has determined that notice and opportunity for prior public comment hereon are impracticable because these procedures would significantly delay issuance of the approval design and thus delivery of the affected aircraft. In addition, the substance of these special conditions has been subject to the public comment process in several prior instances with no substantive comments received. The FAA, therefore, finds that good cause exists for making these special conditions effective upon issuance

Comments Invited

Interested persons are invited to submit such written data, views, or arguments as they may desire. Communications should identify the regulatory docket or notice number and be submitted in duplicate to the address specified above. All communications received on or before the closing date for comments will be considered by the Administrator. The special conditions may be changed in light of the comments received. All comments received will be available in the Rules Docket for examination by interested persons, both before and after the closing date for comments. A report summarizing each substantive public contact with FAA personnel concerning this rulemaking will be filed in the docket. Commenters wishing the FAA to acknowledge receipt of their comments submitted in response to this notice must include a self-addressed, stamped postcard on which the following statement is made: "Comments to Docket No. CE188." The postcard will be date stamped and returned to the commenter.

Background

On November 7, 2001, Rockwell Collins, Incorporated, Cedar Rapids, Iowa 52498 made an application to the

FAA for a new Supplemental Type Certificate for the Raytheon Aircraft Model B300/B300C airplanes. The airplane is currently approved under TC No. A24CE. The proposed modification incorporates the installation of the Rockwell Collins ProLine 21 Display System. The ProLine 21 system will replace the EFIS originally installed on the airplane. Like the original EFIS, the new system has the potential to be vulnerable to high-intensity radiated fields (HIRF) external to the airplane.

Type Certification Basis

Under the provisions of 14 CFR part 21, § 21.101, Rockwell Collins must show that the Raytheon Model B300/ B300C aircraft meets the following provisions, or the applicable regulations in effect on the date of application for the change to the Raytheon Model B300/ B300C. The regulations incorporated by reference in the type certificate are commonly referred to as the "original type certification basis." The regulations incorporated by reference in Type Certificate Data Sheet A24CE are as follows:

Certification Basis FAR Part 23 effective February 1, 1965, as amended by Amendments 23–1 through 23–34; Federal Aviation Regulations part 36 effective December 1, 1969, as amended by Amendment 36-1 through 36-15; SFAR 27 effective February 1, 1974, as amended by Amendments 27-1 through 27-6 and Exemption No. 5077 from compliance with § 23.207(c). Federal Aviation Regulations part 23, § § 23.201, 23.203, and 23.205 through Amendment 23-45 (S/N FN-1 and up only). Effective January 20, 1994, Federal Aviation Regulations § 23.1457 as amended by Amendment 23-35. Exemption 5599 from compliance with § 23.53(c)(1), for use of ground minimum control speed (V_{MCG}) for determination of takeoff decision speed (V1), (Serials FL-111, FM-9, FN-2 and after, or prior airplanes modified by Beech Kit No. 130-3004).

Compliance with ice protection has been demonstrated in accordance with § 23.1419 when ice protection equipment is installed in accordance with the Equipment List. Equivalent Safety Findings: § 23.781(b) for shape of the propeller control knob; § 23.1305(g)

for use of fuel low pressure warning annunciators in lieu of the fuel pressure indicators; § 23.1321(d) for the basic "T" instrument panel arrangement.

Discussion

If the Administrator finds that the applicable airworthiness standards do not contain adequate or appropriate safety standards because of novel or unusual design features of an airplane, special conditions are prescribed under the provisions of § 21.16.

Special conditions, as appropriate, as defined in § 11.19, are issued in accordance with § 11.38 after public notice and become part of the type certification basis in accordance with 14

CFR part 21 § 21.101.

Special conditions are initially applicable to the model for which they are issued. Should the applicant apply for a supplemental type certificate to modify any other model already included on the same type certificate to incorporate the same novel or unusual design feature, the special conditions would also apply to the other model under the provisions of § 21.101.

Novel or Unusual Design Features

Rockwell Collins will incorporate certain novel and unusual design features into the Raytheon Model B300/B300C airplane for which the airworthiness standards do not contain adequate or appropriate safety standards for protection from the effects of HIRF. These features, including EFIS, are susceptible to the HIRF environment and were not envisaged by the existing regulations for this type of airplane.

Protection of Systems from High Intensity Radiated Fields (HIRF): Recent advances in technology have given rise to the application in aircraft designs of advanced electrical and electronic systems that perform functions required for continued safe flight and landing. Due to the use of sensitive solid state advanced components in analog and digital electronics circuits, these advanced systems are readily responsive to the transient effects of induced electrical current and voltage caused by the HIRF. The HIRF can degrade electronic systems performance by damaging components or upsetting system functions.

Furthermore, the HIRF environment has undergone a transformation that was not foreseen when the current requirements were developed. Higher energy levels are radiated from transmitters that are used for radar, radio, and television. Also, the number of transmitters has increased significantly. There is also uncertainty concerning the effectiveness of airframe

shielding for HIRF. Furthermore, coupling to cockpit-installed equipment through the cockpit window apertures is undefined.

The combined effect of the technological advances in airplane design and the changing environment has resulted in an increased level of vulnerability of electrical and electronic systems required for the continued safe flight and landing of the airplane. Effective measures against the effects of exposure to HIRF must be provided by the design and installation of these systems. The accepted maximum energy levels in which civilian airplane system installations must be capable of operating safely are based on surveys and analysis of existing radio frequency emitters. These special conditions require that the airplane be evaluated under these energy levels for the protection of the electronic system and its associated wiring harness. These external threat levels, which are lower than previous required values, are believed to represent the worst case to which an airplane would be exposed in the operating environment.

These special conditions require qualification of systems that perform critical functions, as installed in aircraft, to the defined HIRF environment in paragraph 1 or, as an option to a fixed value using laboratory tests, in paragraph 2, as follows:

(1) The applicant may demonstrate that the operation and operational capability of the installed electrical and electronic systems that perform critical functions are not adversely affected when the aircraft is exposed to the HIRF environment defined below:

Frequency	Field strength (volts per meter)	
	Peak	Average
10 kHz-100 kHz 100 kHz-500kHz	50 50	50 50
500 kHz–2 MHz 2 MHz–30 MHz 30 MHz–70 MHz	50 100 50	50 100 50
70 MHz–100 MHz 100 MHz–200 MHz	50 50 100	50 50 100
200 MHz–400 MHz 400 MHz–700 MHz	100 100 700	100
700 MHz–1 GHz 1 GHz–2 GHz	700 700 2000	100 200
2 GHz–4 GHz 4 GHz–6 GHz	3000 3000	200 200 200
6 GHz–8 GHz 8 GHz–12 GHz 12 GHz–18 GHz 18 GHz–40 GHz	1000 3000 2000 600	200 300 200 200

The field strengths are expressed in terms of peak root-mean-square (rms) values over the complete modulation period.

(2) The applicant may demonstrate by a system test and analysis that the electrical and electronic systems that perform critical functions can withstand a minimum threat of 100 volts rms per meter, electrical field strength, from 10 kHz to 18 GHz. When using this test to show compliance with the HIRF requirements, no credit is given for signal attenuation due to installation.

A preliminary hazard analysis must be performed by the applicant, for approval by the FAA, to identify either electrical or electronic systems that perform critical functions. The term 'critical'' means those functions whose failure would contribute to, or cause, a failure condition that would prevent the continued safe flight and landing of the airplane. The systems identified by the hazard analysis that perform critical functions are candidates for the application of HIRF requirements. A system may perform both critical and non-critical functions. Primary electronic flight display systems, and their associated components, perform critical functions such as attitude, altitude, and airspeed indication. The HIRF requirements apply only to critical functions.

Compliance with HIRF requirements may be demonstrated by tests, analysis, models, similarity with existing systems, or any combination of these. Service experience alone is not acceptable since normal flight operations may not include an exposure to the HIRF environment. Reliance on a system with similar design features for redundancy as a means of protection against the effects of external HIRF is generally insufficient since all elements of a redundant system are likely to be exposed to the fields concurrently.

Applicability

As discussed above, these special conditions are applicable to the Raytheon Model B300/B300C airplanes. Should Rockwell Collins apply at a later date for a supplemental type certificate to modify any other model on the same type certificate to incorporate the same novel or unusual design feature, the special conditions would apply to that model as well under the provisions of § 21.101.

Conclusion

This action affects only certain novel or unusual design features on one model of airplane. It is not a rule of general applicability and affects only the applicant who applied to the FAA for approval of these features on the airplane.

The substance of these special conditions has been subjected to the

or,

notice and comment period in several prior instances and has been derived without substantive change from those previously issued. It is unlikely that prior public comment would result in a significant change from the substance contained herein. For this reason, and because a delay would significantly affect the certification of the airplane, which is imminent, the FAA has determined that prior public notice and comment are unnecessary and impracticable, and good cause exists for adopting these special conditions upon issuance. The FAA is requesting comments to allow interested persons to submit views that may not have been submitted in response to the prior opportunities for comment described above.

List of Subjects in 14 CFR Part 23

Aircraft, Aviation safety, Signs and symbols.

Citation

The authority citation for these special conditions is as follows:

Authority: 49 U.S.C. 106(g), 40113 and 44701; 14 CFR part 21, § 21.16 and § 21.101; and 14 CFR 11.38 and 11.19.

The Special Conditions

Accordingly, pursuant to the authority delegated to me by the Administrator, the following special conditions are issued as part of the type certification basis for the Raytheon Aircraft Company Model B300/B300C airplanes modified by Rockwell Collins to add an EFIS.

- 1. Protection of Electrical and Electronic Systems from High Intensity Radiated Fields (HIRF). Each system that performs critical functions must be designed and installed to ensure that the operations, and operational capabilities of these systems to perform critical functions, are not adversely affected when the airplane is exposed to high intensity radiated electromagnetic fields external to the airplane.
- 2. For the purpose of these special conditions, the following definition applies: *Critical Functions*: Functions whose failure would contribute to, or cause, a failure condition that would prevent the continued safe flight and landing of the airplane.

Issued in Kansas City, Missouri on December 18, 2002.

Michael Gallagher,

Manager, Small Airplane Directorate, Aircraft Certification Service.

[FR Doc. 02–33126 Filed 12–31–02; 8:45 am] BILLING CODE 4910–13–P

DEPARTMENT OF TRANSPORTATION

Federal Aviation Administration

14 CFR Part 23

[Docket No. CE193, Special Condition 23–133–SC]

Special Conditions: S-TEC Corporation; Various Airplane Models; Protection of Systems for High Intensity Radiated Fields (HIRF)

AGENCY: Federal Aviation Administration (FAA), DOT.

ACTION: Final special conditions; request for comments.

SUMMARY: These special conditions are issued to S-TEC Corporation, One S-TEC Way Municipal Airport, Mineral Wells, TX 76067, for a Supplemental Type Certificate for the models listed under the heading "Type Certification Basis." These special conditions include various airplane models to streamline the certification process as recommended from completed Safer Sky Programs. The primary objective of streamlining the certification process is to improve the safety of the airplane fleet by fostering the incorporation of both new technologies that can be certificated affordably under 14 CFR

part 23. The airplanes will have novel and unusual design features when compared to the state of technology envisaged in the applicable airworthiness standards. These novel and unusual design features include the installation of single or dual Meggitt Avionics Magic electronic flight instrument system (EFIS) manufactured by Meggitt Avionics, for which the applicable regulations do not contain adequate or appropriate airworthiness standards for the protection of these systems from the effects of high intensity radiated fields (HIRF). These special conditions contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to the airworthiness standards applicable to these airplanes.

DATES: The effective date of these special conditions is December 18, 2002. Comments must be received on or before before February 3, 2003.

ADDRESSES: Comments may be mailed in duplicate to: Federal Aviation Administration, Regional Counsel, ACE-7, Attention: Rules Docket Clerk, Docket No. CE193, Room 506, 901 Locust, Kansas City, Missouri 64106. All comments must be marked: Docket No. CE193. Comments may be inspected in the Rules Docket weekdays, except

Federal holidays, between 7:30 a.m. and 4:00 p.m.

FOR FURTHER INFORMATION CONTACT: Wes Ryan, Aerospace Engineer, Standards Office (ACE-110), Small Airplane Directorate, Aircraft Certification Service, Federal Aviation Administration, 901 Locust, Room 301, Kansas City, Missouri 64106; telephone (816) 329-4127.

SUPPLEMENTARY INFORMATION: The FAA has determined that notice and opportunity for prior public comment hereon are impracticable because these procedures would significantly delay issuance of the design approval and thus delivery of the affected aircraft. In addition, the substance of these special conditions has been subject to the public comment process in several prior instances with no substantive comments received. The FAA, therefore, finds that good cause exists for making these special conditions effective upon issuance.

Comments Invited

Interested persons are invited to submit such written data, views, or arguments as they may desire. Communications should identify the regulatory docket or notice number and be submitted in duplicate to the address specified above. All communications received on or before the closing date for comments will be considered by the Administrator. The special conditions may be changed in light of the comments received. All comments received will be available in the Rules Docket for examination by interested persons, both before and after the closing date for comments. A report summarizing each substantive public contact with FAA personnel concerning this rulemaking will be filed in the docket. Commenters wishing the FAA to acknowledge receipt of their comments submitted in response to this notice must include a self-addressed, stamped postcard on which the following statement is made: "Comments to Docket No. CE193." The postcard will be date stamped and returned to the commenter.

Background

On September 16, 2002, S—TEC Corporation, One S—TEC Way, Mineral Wells Airport, Mineral Wells, Texas 76067, made an application to the FAA for a new Supplemental Type Certificate for the Raytheon (Beech) 65—90, 55—A90, 65—A90—1, 65—A90—4, B90, and C90 airplane models. They have also identified future STC projects that need the special conditions. All models are currently approved under the type